


## 25 链轮

### 25 SPROCKETS

Pitch 节距: 6.35  
 Inner width 内节内宽: 3.18  
 Roller-φ 滚子直径: 3.30



Dimensions: millimeters

齿数 No. of Teeth	外径 Outside Diam. OD	节径 Pitch Diam. P.C.D	底径 Bottom or Caliper Diam.	B 型单排 Type "B" SINGLE STRAND					A 型 TYPE "A"	
				搭子 HUB		工艺孔 Stock Bore	最大加工孔 Max Bore	重量 Wt. kg	工艺孔 Stock Bore	
				直径 BD	总高 BL					
10	23	20.55	17.25	14	15	6.5	8.5	0.03	9	
11	25	22.54	19.01	15	15	6.5	8.5	0.03	9	
12	28	24.53	21.23	15	15	7.5	9.5	0.03	9	
13	30	26.53	23.04	18	15	7.5	10	0.05	9	
14	32	28.54	25.24	20	15	7.5	10	0.05	9	
15	34	30.54	27.07	20	15	7.5	10	0.05	9	
16	36	32.55	29.25	25	15	9.5	12	0.06	9	
17	38	34.56	31.11	25	15	9.5	12	0.07	9	
18	40	36.57	33.27	25	15	9.5	12	0.07	9	
19	42	38.58	35.15	28	15	9.5	16	0.08	9	
20	44	40.59	37.29	28	15	9.5	16	0.08	9	
21	46	42.61	39.19	28	15	9.5	16	0.09	9	
22	48	44.62	41.32	30	15	9.5	16	0.10	9	
23	50	46.63	43.23	30	15	9.5	16	0.11	9	
24	52	48.65	45.35	30	15	9.5	16	0.12	9	
25	54	50.66	47.27	35	15	9.5	20	0.14	9	
26	56	52.68	49.38	35	15	9.5	20	0.14	9	
27	58	54.70	51.30	35	15	9.5	20	0.15	9	
28	60	56.71	53.41	35	15	9.5	20	0.15	9	
29	62	58.73	55.35	35	15	9.5	20	0.16	9	
30	64	60.75	57.45	35	15	9.5	20	0.16	10	
31	66	62.77	59.39	40	20	10.5	22	0.20	10	
32	68	64.78	61.48	40	20	10.5	22	0.20	10	
33	70	66.80	63.43	40	20	10.5	22	0.20	10	
34	72	68.82	65.52	40	20	10.5	22	0.21	10	
35	74	70.84	67.47	40	20	10.5	22	0.21	10	
36	76	72.86	69.56	40	20	10.5	22	0.22	10	
37	78	74.88	71.51	40	20	10.5	22	0.26	10	
38	80	76.90	73.60	40	20	10.5	22	0.26	10	
39	82	78.91	75.55	40	20	10.5	22	0.27	10	
40	84	80.93	77.63	40	20	10.5	22	0.27	11	
41	87	82.95	79.59	50	20	10.5	30	0.32	11	
42	89	84.97	81.67	50	20	10.5	30	0.32	11	
43	91	86.99	83.63	50	20	10.5	30	0.40	11	
44	93	89.01	85.71	50	20	10.5	30	0.41	11	
45	95	91.03	87.68	50	20	10.5	30	0.41	11	
48	101	97.09	93.79	50	20	10.5	30	0.43	11	
50	105	101.13	97.83	50	20	10.5	30	0.46	11	
54	113	109.21	105.91	50	20	10.5	30	0.47	11	
60	125	121.33	118.03	50	20	10.5	30	0.52	11	
65	135	131.43	128.09	50	30	11.5	30	0.72	11	
70	145	141.54	138.24	50	30	11.5	30	0.77	11	
75	155	151.64	148.31	50	30	11.5	30	0.82	12	
80	165	161.74	158.44	50	30	11.5	30	0.88	12	

NOTE:

- Data in colored box imply teeth hardening.
- Other sprockets than listed may be manufactured. For details, contact us.
- Shaft hole, key groove and tap hole may be machined upon request.